



Get the reliability and flexibility of a professional-grade 3D production system at an affordable price.

With the Fortus 250mc you can produce durable prototypes, manufacturing tools and end-use parts using ABSplus P-430, a production-grade thermoplastic used in real manufacturing applications. Built on a proven Stratasys platform for reliable operation, the Fortus 250mc features a 10 x 10 x 12 inch (254 x 254 x 305 mm) build envelope and three layer thicknesses: .007, .010 and .013 inches (.178, .254 and .330 mm).

The Fortus 250mc is powered by Insight™ job processing and management software which offers users the flexibility to edit standard parameters that control the look, strength and precision of parts, as well as the time, throughput and efficiency of the build process. Like all Fortus 3D Production Systems, the Fortus 250mc utilizes Stratasys Fused Deposition Modeling™ (FDM®) technology to build parts from the bottom up with precisely deposited layers of modeling and support material.

The Fortus 250mc delivers reliable, flexible part production for prototyping and direct digital manufacturing – all at an affordable price.



SYSTEM SPECIFICATIONS

SYSTEM CONFIGURATION													
Build Envelope (XYZ)	10 x 10 x 12 inches (254 x 254 x 305 mm)												
Material Delivery	One (1) Build material cartridge: 56.3 in ³ (923 cc) One (1) Support material cartridge: 56.3 in ³ (923 cc)												
MATERIAL OPTIONS													
Layer Thickness:	ABS plus-P430												
0.013 inch (0.330 mm)	X												
0.010 inch (0.254 mm)	X												
0.007 inch (0.178 mm)	X												
Support Structure:	Soluble												
Available Colors:	<table border="0"> <tr> <td><input type="checkbox"/> Ivory</td> <td><input type="checkbox"/> Red</td> <td><input type="checkbox"/> Fluorescent Yellow</td> </tr> <tr> <td><input type="checkbox"/> White</td> <td><input type="checkbox"/> Blue</td> <td><input type="checkbox"/> Custom Colors</td> </tr> <tr> <td><input type="checkbox"/> Black</td> <td><input type="checkbox"/> Olive Green</td> <td></td> </tr> <tr> <td><input type="checkbox"/> Dark Grey</td> <td><input type="checkbox"/> Nectarine</td> <td></td> </tr> </table>	<input type="checkbox"/> Ivory	<input type="checkbox"/> Red	<input type="checkbox"/> Fluorescent Yellow	<input type="checkbox"/> White	<input type="checkbox"/> Blue	<input type="checkbox"/> Custom Colors	<input type="checkbox"/> Black	<input type="checkbox"/> Olive Green		<input type="checkbox"/> Dark Grey	<input type="checkbox"/> Nectarine	
<input type="checkbox"/> Ivory	<input type="checkbox"/> Red	<input type="checkbox"/> Fluorescent Yellow											
<input type="checkbox"/> White	<input type="checkbox"/> Blue	<input type="checkbox"/> Custom Colors											
<input type="checkbox"/> Black	<input type="checkbox"/> Olive Green												
<input type="checkbox"/> Dark Grey	<input type="checkbox"/> Nectarine												
OTHER SPECIFICATIONS													
System Size/Weight	33 x 29 x 45 inches (838 x 737 x 1143 mm) With crate: 409 lbs. (186 kg) Without crate: 326 lbs. (148 kg)												
Achievable Accuracy	Parts are produced within an accuracy of $\pm .0095$ inch ($\pm .241$ mm)* *Note: Accuracy is geometry dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield.												
Network Communication	10/100 base T connection. Ethernet protocol.												
Operator Attendance	Limited attendance for job start and stop required.												
Operating Environment	Maximum room temperature of 86°F (30°C). Relative humidity range: 30 to 70 percent, non condensing												
Power Requirements	110–120 VAC, 60 Hz, minimum 15A dedicated circuit; or 220–240 VAC 50/60 Hz, minimum 7A dedicated circuit.												
Regulatory Compliance	CE / ETL												
Software	All Fortus systems include Insight™ and Control Center™ job processing and management software.												

At the core: Advanced FDM Technology™

Fortus systems are based on Stratasys FDM — Fused Deposition Modeling™ — technology. FDM is the industry's leading additive manufacturing technology, and the only one that uses production grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization, and high impact applications.

No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems don't produce noxious fumes, chemicals, or waste.

No special skills needed

Fortus 3D Production Systems are easy to operate and maintain compared to other additive fabrication systems because there are no messy powders or resins to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes. Accuracy. Strength. The best way to see the advantages of a Fortus 3D Production System is to have your own part built on a Fortus system. Get your free part at: www.fortus.com/benchmark



3D Solids Additive Manufacturing Technology

575 Grafiet Street, Elardus Park, Pretoria, 0181
P O Box 73, Wingate Park, 0153

Tel : +27 12 345 5112 www.3dsolids.co.za

For more information about Fortus systems, materials and applications, call 888.480.3548 or visit www.fortus.com

Fortus 3D Production Systems
Stratasys Incorporated
7665 Commerce Way
Eden Prairie, MN 55344
+1 888 480 3548 (US Toll Free)
+1 952 937 3000
+1 952 937 0070 (Fax)
info@stratasys.com

Fortus 3D Production Systems
Stratasys GmbH
Weismüllerstrasse 27
60314 Frankfurt am Main
Germany
+49 69 420 994 30 (Tel)
+49 69 420 994 333 (Fax)
europa@stratasys.com

ISO 9001:2008 Certified

©2011 Stratasys Inc. All rights reserved. Stratasys, FDM and Fortus are registered trademarks and Fused Deposition Modeling, FDM Technology, Fortus 250mc, Fortus 360mc, Fortus 400mc, Fortus 900mc, Insight, Control Center and FDM TEAM are trademarks of Stratasys Inc., registered in the United States and other countries. *ULTEM 9085 is a trademark of SABIC Innovative Plastics IP BV. All other trademarks are the property of their respective owners. Product specifications subject to change without notice. Fortus-SS-250mc-01/13

FORTUS
3D PRODUCTION SYSTEMS